

## WVLF-60M-1G01A

### Product Feature

- High Reliability
- RoHS Compliant

### Electrical Specifications

<b>Passband Frequency</b>	60MHz ~ 1000MHz
<b>Insertion Loss at Passband</b>	1.5dB Max. @ 60MHz ~ 65MHz 1.2dB Max @ 65MHz ~ 1000MHz
<b>Ripple at Passband</b>	1.5dB Max. @ 60MHz ~ 65MHz 1.2dB Max @ 65MHz ~ 1000MHz
<b>Return Loss at Passband</b>	14.0dB Min
<b>Rejection</b>	50dB Min @ 1~40MHz 40dB Min @ 40 ~ 50MHz
<b>Power Handling (CW)</b>	+80W CW Max
<b>In/Out Impedance</b>	50 Ohms Nominal

### Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +85 °C, IP67
------------------------------	------------------------

### Mechanical Specifications

<b>Dimension</b>	150.0 x 70.0 x 30.0 (Unit: mm)
<b>Mounting Points</b>	See Outline Drawing
<b>RF Connector</b>	Input : N Female Connector Output : N Female Connector
<b>Connector Position</b>	See Outline Drawing
<b>Finish</b>	White Color Chromate

# LC-HPF

## ◆ OUTLINE DRAWING

